

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number  
**WO 2005/022030 A2**

(51) International Patent Classification<sup>7</sup>: **F21K 7/00**

(21) International Application Number:  
PCT/IB2004/051431

(22) International Filing Date: 9 August 2004 (09.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03103253.5 29 August 2003 (29.08.2003) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ANSEMS, Johannes, P., M.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **HOELEN, Christoph, G., A.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **JUESTEL, Thomas** [DE/DE]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: **VAN DER VEER, Johannis, L.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: COLOR-MIXING LIGHTING SYSTEM



(57) Abstract: A color-mixing lighting system has a light-emitting diode (6, 7) emitting first visible light having a first peak wavelength in a first spectral range and has a fluorescent material (8) converting a portion of the first visible light into second visible light having a second peak wavelength in a second spectral range. The second visible light has a full width at half maximum (FWHM) of at least 50 nm. Preferably, the second visible light is red light, the second peak wavelength being in the range from 590 to 630 nm, preferably, in the range from 600 to 615 nm. Preferably, the lighting system comprises a further light-emitting diode (7) for emitting third visible light having a third peak wavelength in a third spectral range. The color-mixing lighting system according to the invention generates white light with a high color-rendering index and allows certain variations in the wavelength of the primaries.

WO 2005/022030 A2



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*